

Profile	BBS02	
BASIC		
Low Battery Protection [Volts]	41	
Current Limit [Amps]	25	
Assist Levels	Current Limit [%]	Speed Limit [%]
Assist 0	1	1
Assist 1	52	44
Assist 2	58	51
Assist 3	64	58
Assist 4	70	65
Assist 5	76	72
Assist 6	82	79
Assist 7	88	86
Assist 8	94	93
Assist 9	100	100
Speed Meter Type	External, Wheel Sensor	
Speed Meter Signals	1	
Wheel Diameter [Inch]	18	
PEDAL ASSIST		
Pedal Sensor Type	Double Signal 24	
Designated Assist Level	By Display's Command	
Speed Limit	By Display's Command	
Start Current [%]	10	
Slow-start Mode (1-8)	4	
Crank Trigger Pulses	2	
Work Mode (Crank Speed/Wheel*10)	Undetermined	
Stop Delay [x10ms]	5	
Current Decay (1-8)	8	
Stop Decay [x10ms]	0	
Keep Current [%]	100	
THROTTLE		
Start Voltage [x100mV]	11	
End Voltage [x100mV]	35	
Mode	Speed	
Designated Assist Level	9	
Speed Limit	40 km/h 24.9 mph	
Start Current [%]	10	