

# System Operation Manual

## **E3 Path+, Venture, Detour**

This manual is meant to be read together with the owner's manual, also included with your bicycle. The owner's manual contains important safety and use information about your bicycle. Be sure to read both manuals before riding for the first time, or performing any assembly. If you did not receive an owner's manual, the most recent version can always be found online at [www.CurrieTech.com](http://www.CurrieTech.com).




EBCC Technical and Customer Service: +1 800-377-4532

# Contents

<b>Section 1</b>	Electrical System Components . . . . .	4
<b>Section 2</b>	General information . . . . .	8
<b>Section 3</b>	Basics . . . . .	10
	Battery charging . . . . .	10
	<i>Charging procedure</i> . . . . .	10
	<i>Charge time</i> . . . . .	10
	<i>Checking the battery's charge level</i> . . . . .	10
	Using the battery . . . . .	11
	<i>Installing the battery</i> . . . . .	11
	<i>Removing the battery.</i> . . . . .	11
	<i>Turning the bike on and off.</i> . . . . .	11
	<i>To turn the bike on...</i> . . . . .	11
	<i>To turn the bike off...</i> . . . . .	11
<b>Section 4</b>	Riding and use . . . . .	12
	Getting ready to ride . . . . .	12
	Riding the bike . . . . .	12
	<i>Using the motor.</i> . . . . .	12
	<i>Assist levels</i> . . . . .	12
	<i>Throttle</i> . . . . .	12
	<i>Cruise control.</i> . . . . .	13
	<i>Using the brakes</i> . . . . .	13
	The display and control pad . . . . .	13
	<i>The display's cyclecomputer functions.</i> . . . .	13
	<i>The display's electrical system functions.</i> . . . .	14
	<i>Assist level</i> . . . . .	14
	<i>Battery level</i> . . . . .	14
	<i>Maintenance information</i> . . . . .	14
	<i>Control pad functions.</i> . . . . .	14
<b>Section 5</b>	Troubleshooting . . . . .	15
	Error codes . . . . .	15
	Charging issues . . . . .	15
	Misc issues . . . . .	16
	<i>Lost key.</i> . . . . .	16

# Notice!




**Your bike ships without the battery fuse installed.** This helps keep the battery in top condition during shipping and storage. **Before using your bike for the first time,** you'll need to **install the fuse,** as shown in the diagram above.

The fuse is in a small plastic bag, either hanging from the bike or in the parts box. It is a standard 30-Amp automotive fuse.

# Electrical System Components


## Battery and rack



## Control pad

### CONTROL PAD BUTTONS

A	Assist level
B	Light
C	Power
D	Info
E	Cruise control




*Operational details, see p.12-14*


## Display

### DISPLAY FUNCTIONS


A	Ambient light sensor
B	Main display area
C	Speed
D	Odometer
E	Distance
F	Range
G	Maintenance indicator
H	Distance unit
I	Assist level indicator
J	Cruise control indicator
K	Low battery warning indicator
L	Battery level indicator




## Throttle



## Battery charger



## Rear wheel





# General information

## USE RESTRICTIONS

<b>Intended Use<sup>1</sup></b>	Condition 2 (General purpose riding)
<b>Minimum rider age</b>	16 years
<b>Maximum permissible weight<sup>2</sup></b>	110 Kg (242 lbs)

1. This bicycle is intended to be used under the guidelines of the stated condition, found in the intended use section of your owner's manual. Be sure to read this section of the owner's manual for more information.

2. Maximum permissible weight includes the weight of the rider (plus clothing, riding gear, etc), the weight of any added accessories, and any cargo being carried.



## TECHNICAL SPECIFICATIONS

### Motor

<b>Type</b>	Rear hub drive
<b>Rated power</b>	500w
<b>Peak torque</b>	42 Nm

### Battery

<b>Voltage</b>	48V nominal
<b>Capacity</b>	8.8Ah
<b>Energy</b>	422Wh
<b>Cycle life (expected)</b>	~700

### Charger

<b>Input voltage</b>	110-240V AC (auto-sensing)
<b>Frequency</b>	50/60Hz
<b>Input current</b>	2.2A maximum
<b>Charging voltage</b>	54.6V DC (48V nominal)
<b>Charging current</b>	2.0A
<b>Full charge duration</b>	4-6 hours

### Ride performance

<b>Top assisted speed</b>	32 km/h (20 mph)
<b>Range (expected)<sup>1</sup></b>	25-35 miles
<b>Control type</b>	Throttle/pedal assist. Cadence sensor, speed sensor.

1. With normal pedaling; Contingent on terrain, rider weight, riding style, and other factors.

# Basics

**IMPORTANT:** The owner's manual included with your bike contains most of the important safety and usage information about this bike, which is not included in this system operation manual. Be sure to read the owner's manual before you begin riding or working on your bike.

## Battery charging

You should charge the battery fully before riding for the first time, following the instructions below. Be sure to check the section of your owner's manual discussing "Battery care & safety" for additional information.

### Charging procedure

Connect the power cord to the battery charger. Plug the charging plug into the battery's charging port, then plug the wall plug into a wall outlet.

**The charger should always be plugged first into the battery, then into the wall outlet.**

Charging will begin immediately. The charger's LED indicator will light up to show its status.

LED	STATUS
<b>Red</b>	Charging
<b>Green</b>	Finished charging
<b>Red (flashing)</b>	Charging error; see "Charging issues" below

If the battery is attached to the bicycle, and the bicycle is turned on, the battery level indicator on the bike's display will show the current charge level. See "Turning the bike on and off" on page 11.

The battery does not have a "memory". This means that it can be charged at any time, or partially charged, without causing damage or decreasing performance.

## Charge time

The amount of time needed to charge the battery varies based on the battery's charge level. A completely empty battery will take between 4 and 6 hours to charge. A battery at 50% may only need 2-3 hours to come to a full charge.

## Checking the battery's charge level

Before riding, you should check the battery's charge level. If the battery is not fully charged, riding range will be reduced.

To check the battery's charge level, first install the battery in the bike, then turn the bike on (see "Using the battery" on page 11). The battery level indicator on the display will show the battery's charge level.

Each bar represents about 20% capacity:

BARS	BATTERY CHARGE
(low battery warning)	<5%
1	≤20%
2	~20– 40%
3	~40 – 60%
4	~60 – 80%
5	~80 – 100%

## Using the battery

### Installing the battery

First, make sure the battery is unlocked. If needed, unlock the battery by turning the key 45° counter-clockwise until it stops.

Then, slide the battery into the rack from the rear; the end of the battery will be flush with the battery receiver when fully inserted.

Finally, lock the battery in place by turning the key 45° clockwise.


**You must lock the battery before riding the bike. If the battery is unlocked, it could fall out while you ride.**

### Removing the battery


To remove the battery, first unlock it, then pull it straight out the back of the rack.

## Turning the bike on and off

### To turn the bike on...

Press the control pad power button (  ). The display will initialize, displaying a countdown on its screen. During this countdown, the software is self-testing and calibrating the bike's sensors. While this countdown is shown, do not step on the pedals. The calibration includes setting a zero-point for the pedal sensors, and any weight on the pedals will disrupt this process. After the countdown completes, the bike is ready to ride.

### To turn the bike off...

Press the control pad power button (  ) two times. A, for 2 seconds each time. After the first press, the bike will enter assistance level 0, showing '0' on the display's assist level indicator (see "Assist levels" on page 12). After the second press, the bike will turn off and the display screen will go blank, as will the battery power indicator.

# Riding and use

Be sure to read the “Electric Bikes” section of your owner’s manual, and specifically pay attention to the sections on “Riding an electric bike” and “Riding a high-speed electric bicycle” before you ride for the first time.

## Getting ready to ride

First turn the bike on, following the instructions in “Turning the bike on and off” on page 11 of this manual.

Mount the bicycle. Be sure you don’t accidentally twist the throttle, or turn the pedals; this could cause the bike to accelerate unexpectedly.

## Riding the bike

### Using the motor

The purpose of the motor is to gently augment the effort you put into riding the bike. When you pedal fast, the motor assists you more; when you pedal slowly, the motor assists you less.

So, to ride the bike, all you really need to do is pedal. The majority of the work of controlling the motor is done automatically.

There are, however, three other controls that affect how the motor runs: assist levels, the throttle, and cruise control.

### Assist levels

Assist levels control *how much* power the motor will add to your pedaling. The assist level is shown on the display, and can be changed at any time using the **+** and **-** buttons on the control pad (see “Control pad functions” on page 14).

Levels 1–4 are increasing levels of automatic motor assist. Level 1 gives the least assistance; level 4 gives the most.

“T”, or “throttle-only” mode disables the

automatic motor assist, but leaves the throttle active. Simply twist the throttle to control the motor.

Level 0 disables motor assist completely. Other functions such as the cyclecomputer can still be used.

### Throttle

The throttle can be used under certain conditions to override the automatic assist:


In “T”/throttle-only mode, automatic motor assist is disabled, and the throttle is always active.


In assist level 1–4, when moving under 10 km/h (6 mph), the throttle is always active, even without pedaling. This helps you get moving from a stop, and helps when navigating difficult terrain at low speed.


In assist level 1–4, when moving over 10 km/h (6 mph), the throttle is active as long as you are pedaling.

The throttle is never affected by assist level. Using the throttle, you always have control of up to 100% of the motor’s power.

## Cruise control

While in “T”/throttle-only mode, cruise control can be turned on with the  button:

First, pedal or use the throttle to reach your desired cruising speed. Hold the throttle in a position that maintains this speed, and press the  button. You can then release the throttle, and the bike will hold its current speed, plus or minus about 3 km/h (2 mph).

Cruise control can be disabled at any time by pulling either brake lever, twisting the throttle, or by pressing the  button again.

Cruise control will not function over 32 km/h (20 mph). If you turn on cruise control while traveling faster than 32 km/h, the bike will decelerate to 32 km/h and hold that speed.

## Using the brakes


The brakes are integrated with the electrical system. When you pull the brakes, they not only slow the wheel like a normal bicycle brake, they also cut power from the motor.

See the “Brakes” section of your owner’s manual for more information.

## The display and control pad

The display serves both as a cyclecomputer, displaying speed and distance information, and as an interface to the bike’s electrical system. The functions of the display are controlled by the control pad.


### The display’s cyclecomputer functions


The display has four cyclecomputer functions. Switch between these functions using the  button. The function’s information is displayed in the main display area.

#### CYCLECOMPUTER FUNCTIONS

<b>SPD</b>	<b>Speed</b>	The bicycle’s current speed
<b>ODO</b>	<b>Odometer</b>	The bicycle’s total mileage
<b>DST</b>	<b>Trip distance</b>	The distance covered during the current trip
<b>Range</b>	<b>Remaining range</b>	The estimated remaining range before the battery is empty

Distance and range are displayed in the units shown to the right of the main display area.

To reset the trip distance counter, hold **+** and **-** and  on the control pad together for 10 seconds.

To reset the odometer, hold **+** and **-** and  on the control pad together for 60 seconds.

**The display’s electrical system functions**

The display shows information about the bike’s electric assist, and gives the rider access to several important functions:

**Assist level**

The current assist level is shown on the display (assist level indicator).

**Battery level**

The battery level indicator shows the current charge level of the battery. Each bar represents about 20% capacity.

The low battery warning indicator lights up when the battery has less than 5% remaining charge.





**Maintenance information**

The maintenance indicator lights up when there is a system error. An error code shown on the display helps to diagnose the problem. See “Error codes” below.

**Control pad functions**

The control pad is used to control the various functions of the bike and display.

The control pad’s four buttons perform the following functions:

CONTROL PAD FUNCTIONS	
	Increase assist level (1–4), or to switch to throttle pure mode “T”. Hold 2 seconds for backlight (and light set if installed).
	Decrease assist level (4-1).
	Turn bike on, one quick press (turn on battery first, p.4)
	Change cyclecomputer display, quick presses to cycle through the options (after bike is on)
	Set power assist to 0, one 2 second press (no pedal or throttle assistance, just power for the display)
	Turn power off, one 2 second press (must be in assist level 0 first)
	Activate cruise control.

The display backlight and any attached headlight/taillight is also controlled by the ambient light sensor; they will automatically turn on in low light.

# Troubleshooting

## Error codes

### SYSTEM ERROR CODES

In the event of a system error, these codes will appear on the display.

1	Motor internal error
4	Cadence sensor error
5	Motor speed sensor malfunction
6	Brake lever cut-off sensor malfunction
7	Throttle malfunction

Most of the time, these errors can be resolved easily by checking the wiring connections for the affected component. Call EBCC customer service, or see your dealer for more information.

## Charging issues

### ISSUE: Charger LED indicator flashes red

LED flashes red after charging for a while:

- ▶ Battery is not responding to charging.
  - The battery voltage is less than 25V, and does not rise above 25V after 30 minutes of charging.
  - The battery voltage is between 25V and 30V, and does not rise above 30V after one hour of charging.

Solution	▶ Reset charging by unplugging the charger from the wall outlet, then plugging it back in. If charging fails after a second attempt, the battery or charger may need to be replaced. Bring them to your dealer for inspection.
----------	--

- ▶ Battery has not finished charging after 10 hours.

Solution	▶ The battery may be damaged and should be inspected by your dealer.
----------	--

LED flashes red immediately after being plugged in:

- ▶ The polarity between the charger and battery does not match.

Solution	▶ The battery or charger may be damaged. Stop using the battery and charger immediately, and bring them to your dealer for inspection.
----------	--

- ▶ The output of the charger is short-circuited.

Solution

▶

 Stop using the battery and charger immediately. Check for obvious external shorts on the charging plug and battery charging port. If no obvious short exists, the battery or charger may be damaged. Bring them to your dealer for inspection.

Other issues causing a flashing red LED:

▶

 The temperature of the battery is too high to charge.

Solution

▶

 Put the battery and charger in a cool place, then try charging again after a few minutes.

ISSUE: Charger LED indicator stays green when plugged into the battery.

▶

 There is no connection between the charger and the battery.

Solution

▶

 Check for damage: battery charging port, charging plug, charging cord, and power cord.

▶

 There may be an internal problem with the battery or charger. Bring them to your dealer for inspection.

▶

 The battery's voltage is too low to be charged.

Solution

▶

 Check the battery's charge level as described in this document. If the battery will not turn on, the battery may be damaged and should be inspected by your dealer.

## Misc issues



### Lost key

If you have lost your keys, note your bike's serial number (located underneath the frame's bottom bracket) then call EBCC customer service at (800) 377-4532.

### No power from battery

The battery has a user-replaceable fuse located at its base. The fuse is not installed at the factory; you must install it before using the bike for the first time.

If the fuse is present but the bike still does not power up, inspect the fuse; if it is blown out, it can be replaced with a standard 30-amp automotive fuse.



Good

Blown