

Trek 7200

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Titanite Black/ Coastal Blue • Blue/silver/black decal • Black fork	
Fork	RST CT COM 1 C4	50 mm travel, 456.9 mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36 mm stack height

CONTROLS

Handlebar	Steel	25.4 mm clamp diameter
Stem	Alloy adjustable rise	
Shift levers	SRAM MRX Plus	
Brake levers	Alloy, direct pull	
Grips	Kraton	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, (W-down), 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano C203 48/38/28, w/chainguard	64/104 mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 120 (shell x axle, mm), Square axle
Chain	IG-51	3/32", 114 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 750 rim	604mm E.R.D.
	295 mm 3x spokes, Rubber rim strip	
Rear wheel	Shimano RM-40 hub, 36°, Matrix 750 rim	604 mm E.R.D.
	292/293 mm 3x rear spokes, Rubber rim strip	
Spokes	14G stainless	
Front tire	Bontrager Select Invert	700 x 35c
Rear tire	Bontrager Select Invert	700 x 35c
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2 mm outer diameter
Saddle	Bontrager Webspring Comfort	
Seatpost binder . . .	Alloy w/integral QR	31.8 mm inner diameter
Brakes	Alloy direct pull w/modulator front, Alloy direct pull rear	
Pedals	Platform, dual density	9/16" axle
Additional	2 water bottle mounts (1 on 15, 15W), rack mounts (not 15)bell on brake lever	
Bike weight	30.8 lb/13.98 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	15	17.5	20	22.5	25	15W	17W	20W
Rider height, in.		69.9	70.6	72.0	73.8	74.1	70.2	70.8	72.6
	cm	178	179	183	187	188	178	180	184
Handlebar	width	600	600	620	620	620	600	600	620
Handlebar	rise	50	50	50	50	50	50	50	50
Stem	length	115	115	115	115	115	115	115	115
	angle	30	30	30	30	30	30	30	30
Headset	spacers	2	2	2	2	2	2	2	2
Crank	length	170	170	170	170	170	170	170	170
Seatpost	length	350	350	350	350	350	350	350	350
Steerer	length	129	144	144	164	184	144	164	184

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	70.5	71.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	78	78	71	65	65	78	78	71
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	74.0	73.5
Effective top tube	548	552	568	584	596	546	550	566
Seat tube	381	445	508	572	635	381	432	508
Standover	693	737	778	825	872	596	589	574
Wheelbase	1058	1057	1057	1058	1058	1057	1057	1057
Bottom bracket height	288	288	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445	445	445
Head tube	90	105	105	125	145	105	125	145

GEARING

	28	38	48
11	70	95	120
12	64	87	110
14	55	74	94
16	48	65	82
18	43	58	73
21	37	50	63
26	30	40	51
32	24	33	41